



- Note:**
- Standard 1050 to 1200 manhole tee-offs pipe are available as shown. Custom options are available upon request.
 - Reinforced concrete pipe is manufactured to meet ASTM C76 specifications.
 - Manhole manufactured to ASTM C478 and CSA 257.4 specifications.
 - Supplied with ladder rungs as shown.
 - Different pipe sizes and manhole risers are available.
 - Minimum concrete strength meets or exceeds ASTM specifications.
 - Supplied with a Starcon-style lifting insert as required.
Note: Sling angle to vertical must not exceed 15°.
 - Unit supplied with Tylox SuperSeal Gasketed Joint for water & Silt tight.
 - All dimensions are in millimeters unless otherwise specified.

Amrize Canada Inc. BC Pipe and Precast are certified Q-Cast Plants, an American Concrete Pipe Association Third Party Certification for the manufacture of Pipe, Manhole, Box Culvert and Precast Items.

Quality Assurance of products manufactured by Amrize Canada Inc. BC Pipe and Precast has been verified by the following third party certification programs.



All Dimensions are in Millimeters. Unless otherwise Stated

Projection Method: THIRD ANGLE

AMRIZE

www.amrize.com
CHILLIWACK 1-800 667-9600 / (604) 533-1656
DUNCAN (250) 478-9581

This drawing is the property of the Amrize Canada Inc. All information contained here in is confidential and may not be used in whole or in part without written permission from the owner.

DESCRIPTION:

Pipe Detention Tank

DRAWN BY:	SR	DWG NO.:	PDT
CHK BY:	MP	JOB NO.:	
DATE:	11-Jul-25	SO NO.:	N/A
SCALE:	1:55	REV.:	
SIZE:	11 x 17	SHEET 1 OF 1	